

# SAMLONGDA Plastic Industrial Co., Ltd.

Tel:+86 757 6336 9178 Fax:+86 757 8852 1200 Email: info@samlongda.com

## Nylon Tubing / PA6 / PA 11 / PA 12

Nylon tubing is a type of plastic tubing that is strong and resists abrasion. Nylon tubing is typically used in high-temperature situations or when high pressure is needed. Nylon tubing can be used on air lines, grease lines, high pressure gas lines, brake controls and lubrication lines. It can also function with the use of some diluted acids, organic solvents, hydraulic fluids, and oils. Nylon tubing is often preferred for pneumatic line and low-pressure lines. Nylon tubing also features high-impact resistance and resistance to abrasion, even at very low temperatures.



Code	Size(mm)		W.P.(Mpa)	B.P. (Mpa)	Tolerances MM	Standard Length(m)	Bend Radii (mm)
	O.D	I.D					
P60302	3	2	2.5	2.8	±0.10	100	18
P60425	4	2.5	2.7	4.2	±0.10	100	20
P60402	4	2	3.2	6.0	±0.10	100	30
P60503	5	3	2.3	4.8	±0.10	100	35
P60604	6	4	3.1	6.2	±0.10	100	40
P60806	8	6	2.5	4.5	±0.10	100	50
P61008	10	8	2.6	4.8	±0.10	100	65
P61075	10	7.5	2.5	4.5	±0.10	100	65
P61209	12	9	2.5	4.5	±0.10	100	70
P61612	16	12	1.8	3.6	±0.15	100	80

\*Our factory can supply PA 6, PA11 and PA12 tubing with OEM service.

\*Other sizes are available in our factory, please contact us for more infos

\* All nylon tubings have no stocklots, MOQ 30,000m/size/colour.